

EASY-SLOPE STEEL MOBILE SAFETY STAIRS



- ▶ High quality and very sturdy Safety Stairs manufactured in the UK from heavy grade tubular steel.
- ▶ Extremely safe, stable and robust in use.
- ▶ Constructed from the same materials as our standard Heady Duty models but with two important differences -
 - ▶ **an even shallower rake angle of just 48 degrees**
 - ▶ **a tread-to-tread height of just 230mm**
 - ▶ **These special features make ascent and descent even easier and safer - especially when carrying heavy objects.**
 - ▶ **Ideal where safety is paramount and space for manoeuvring is plentiful**
- ▶ Ideal for maintenance work and access in storage areas.
- ▶ Large treads of robust punched steel are 700mm wide x 200mm deep for security and comfort (non-slip PVC covered treads are available as a cost option).
- ▶ Large platform 16" / 400mm deep is surrounded by a 3ft / 900mm high handrail on three sides plus half-height midrail. Toeplates fitted around platform on all models.
- ▶ Rubber tyred wheels fitted at the front with swivelling castors at the rear for easy manoeuvring.
- ▶ Braked by the bright yellow integral Ascent Safety Bar. This blocks access to stairs whilst mobile. When pushed back, the castors are automatically raised from the ground to stabilise the stair and allow access to the platform.
- ▶ Many variations to the standard range are available, see over.
- ▶ Coated in a tough and attractive red epoxy-powder finish for long-lasting protection. Hot-Dipped Galvanised finish for outdoor applications is available as a cost option - please enquire.

EASY-SLOPE STEEL MOBILE SAFETY STAIRS					
CODE	Treads including platform	Platform Height	Tread Width mm / ft	Overall Dimensions H x L x W (m)	Appx Weight
overall width 0.87m / 2' 8"					
MSES03	3	0.69m / 2' 3"	700 / 2' 4"	1.69 x 1.13 x 0.87	40kg
MSES04	4	0.92m / 3' 0"	700 / 2' 4"	1.92 x 1.34 x 0.87	50kg
MSES05	5	1.15m / 3' 9"	700 / 2' 4"	2.15 x 1.55 x 0.87	62kg
MSES06	6	1.38m / 4' 6"	700 / 2' 4"	2.38 x 1.76 x 0.87	73kg
overall width 0.95m / 3' 1"					
MSES07	7	1.61m / 5' 3"	700 / 2' 4"	2.61 x 1.78 x 0.93	94kg
MSES08	8	1.84m / 6' 0"	700 / 2' 4"	2.84 x 1.99 x 0.93	104kg
MSES09	9	2.07m / 6' 10"	700 / 2' 4"	3.07 x 2.19 x 0.93	113kg
MSES10	10	2.30m / 7' 7"	700 / 2' 4"	3.30 x 2.40 x 0.93	120kg
overall width 1.08m - 1.11m (varies)					
MSES11	11	2.53m / 8' 4"	700 / 2' 4"	3.53 x 2.61 x 1.08	132kg
MSES12	12	2.76m / 9' 1"	700 / 2' 4"	3.76 x 2.82 x 1.11	142kg
Tread Options - instead of standard Punched Steel (as above)					
For PVC Covered Non-Slip treads change code to "MSEPxx"					
For Hot-Dipped Galvanised finish to "Easy-Slope" Mobile Stairs - please enquire					
A current, detailed price list can be printed from our website www.ladders999.co.uk					

FAX : 01452 505580 TEL: 01452 520144

www.ladders999.co.uk

sales@lansfordaccess.co.uk



National Sales Office - Unit 10 Chancel Close, Eastern Avenue, Gloucester. GL4 3SN

MOBILE SAFETY STAIRS - SPECIFICATIONS

	MEDIUM DUTY range	HEAVY DUTY range	EASY-SLOPE range	Notes
Staircase Angle	60 degrees	55 degrees	48 degrees	Lower angles are easier & safer to descend
Rise per Tread	250mm	250mm	230mm	
Tread Depth	190mm	200mm	200mm	Deeper treads easier
Tread Width (standard)	550mm (Narrow Aisle = 450mm)	to 6tr = 500mm 7tr + = 700mm	700mm	options available
Top Platform Depth (standard)	380mm (2 x 190)	400mm (2 x 200)	400mm (2 x 200)	options available in 190 or 200mm
Tread Surface (standard)	punched steel	punched steel	punched steel	option for PVC covered treads (or alloy chequer plate on HD)
Main Tubes	1" diam x 16g (1.5mm thick)	1" diam x 12g (2.5mm thick)	Rectangular Box 50 x 25 x 2mm	
Braking	to 6tr = 2 x spring loaded castors & 2 x 160mm wheels 7tr + = Ascent Safety Bar Narrow Aisle models = 4 x spring loaded castors	All sizes - Ascent Safety Bar	All sizes - Ascent Safety Bar	option for Side Lever instead of Ascent Safety Bar
Toeplates at Platform	up to 6tr = front toeplate only 7tr + = 3 sided toeplates	All sizes - 3 sided toeplates	All sizes - 3 sided toeplates	
Handrails	up to 6tr = no mid-height rail at platform 7tr + = mid-rail as standard	All sizes - Mid-height rail at platform as standard	All sizes - Mid-height rail at platform as standard	options available for gates, chains, bars etc at platform ; single-sided handrail or no
Finish	2tr - 12tr = epoxy powder coated (blue) 13tr + = wet paint finish unless supplied "knock-down"	epoxy powder coated (red)	epoxy powder coated (red)	colour options available (+ Hot-Dip Galvanised on HDuty & EasySlope)
Fabrication	Made in 1 piece & fully welded ("knock-down" option available)	3tr - 6tr = 1 piece welded as Medium Duty 7tr + = 3 pieces bolted together but supplied assembled for use	3tr - 6tr = 1 piece welded as Medium Duty 7tr + = 3 pieces bolted together but supplied assembled for use	
Safe Working Load	150kg	150kg	150kg	
"Knock-Down" models	normally supplied assembled for use ; if dismantle, needs spanners to bolt together in about 15 minutes ;			
Availability	normally made to order in approx 2 weeks but often a few assorted models in stock			

fax : 01452 505580

tel : 01452 520144

www.ladders999.co.uk

sales@lansfordaccess.co.uk

