

MEDIUM-DUTY STEEL MOBILE SAFETY STAIRS



- ▶ High quality Safety Steps manufactured in the UK from tubular steel, with punched steel treads (PVC covered treads available as a cost option - see below).
- ▶ Coated in a tough and attractive blue epoxy-powder finish for long-lasting protection (models with 12treads and above have traditional wet spray paint finish).
- ▶ Steel treads are 190mm / 7.5" deep and fitted at 250mm rise.
- ▶ Large platform 15" / 380mm deep is surrounded by a 3ft / 900mm high handrail on three sides plus half-height midrail. Toeplates fitted around platform on models with platform height over 2.0m.
- ▶ Rubber tyred wheels fitted at the front with swivelling castors at the rear for easy manoeuvring.
- ▶ 2 - 6 tread models have 2 spring-loaded castors at rear for instant braking when weight is applied.
- ▶ 7 - 15 tread models are braked by the integral Ascent Safety Bar. This blocks access to stairs whilst mobile. When pushed back, the castors are automatically raised to stabilise the stair and allow access to the platform.
- ▶ Many variations to the standard range are available, including single-sided handrails; alternative tread widths; hinged gate at platform; side operating lever etc. Please enquire for details.
- ▶ Ideal for the office, maintenance in the workshop and access in storage areas.
- ▶ Fully welded and assembled for instant use, but can be supplied in optional "Knock-Down" form for ease of transport and for access into awkward areas on site.

NARROW AISLE
version
available for
confined
areas.

Sizes 2 tread
to 6 tread
only.

Overall Width
reduced to
0.50m
(2tr - 4tr)
or

0.63m
(5tr - 6tr).

Full details are
on web page -

see codes
"MSNASxx".



MEDIUM-DUTY STEEL MOBILE SAFETY STEPS

CODE	Treads Including platform	Platform Height	Tread Width mm / ft	Overall Dimensions H x L x W (m)	Appx Weight
overall width 0.70m / 2' 4" - spring-loaded castors at rear for braking					
MSMS02	2	0.50m / 1' 8"	550 / 1' 10"	1.42 x 0.58 x 0.70	16kg
MSMS03	3	0.75m / 2' 6"	550 / 1' 10"	1.67 x 0.74 x 0.70	22kg
MSMS04	4	1.00m / 3' 3"	550 / 1' 10"	1.92 x 0.90 x 0.70	26kg
overall width 0.84m / 2' 9" - spring loaded castors at rear for braking					
MSMS05	5	1.25m / 4' 1"	550 / 1' 10"	2.17 x 1.11 x 0.84	36kg
MSMS06	6	1.50m / 4' 11"	550 / 1' 10"	2.42 x 1.27 x 0.84	40kg
overall width 0.85m / 2' 10" - Ascent Safety Bar for braking					
MSMS07	7	1.75m / 5' 9"	550 / 1' 10"	2.78 x 1.35 x 0.85	62kg
MSMS08	8	2.00m / 6' 7"	550 / 1' 10"	3.01 x 1.51 x 0.85	66kg
MSMS09	9	2.25m / 7' 5"	550 / 1' 10"	3.26 x 1.67 x 0.85	70kg
overall width 1.00m / 3' 4" - Ascent Safety Bar for braking					
MSMS10	10	2.50m / 8' 3"	550 / 1' 10"	3.51 x 1.84 x 1.00	75kg
MSMS11	11	2.75m / 9' 0"	550 / 1' 10"	3.78 x 2.13 x 1.00	86kg
MSMS12	12	3.00m / 9' 10"	550 / 1' 10"	4.01 x 2.27 x 1.00	90kg
overall width 1.16m - 1.32m (varies) - Ascent Safety Bar for braking					
MSMS13	13	3.25m / 10' 8"	550 / 1' 10"	4.26 x 2.35 x 1.16	108kg
MSMS14	14	3.50m / 11' 6"	550 / 1' 10"	4.51 x 2.51 x 1.23	113kg
MSMS15	15	3.75m / 12' 4"	550 / 1' 10"	4.76 x 2.66 x 1.32	118kg
Tread Options - instead of standard Punched Steel (as above)					
For PVC Covered Non-Slip treads change code to "MSMPxx"					
For Narrow Aisle version of Medium Duty Steps (2 - 6 tread sizes) - please enquire					

fax : 0117 951 5682

tel : 0117 935 4664

www.ladders999.co.uk

sales@lansfordaccess.co.uk



National Sales Office - 8A East Park Trading Estate, Gordon Road, Fishponds, BRISTOL BS5 7DR

MOBILE SAFETY STAIRS - SPECIFICATIONS

	MEDIUM DUTY range	HEAVY DUTY range	EASY-SLOPE range	Notes
Staircase Angle	60 degrees	55 degrees	48 degrees	Lower angles are easier & safer to descend
Rise per Tread	250mm	250mm	230mm	
Tread Depth	190mm	200mm	200mm	Deeper treads easier
Tread Width (standard)	550mm (Narrow Aisle = 450mm)	to 6tr = 500mm 7tr + = 700mm	700mm	options available
Top Platform Depth (standard)	380mm (2 x 190)	400mm (2 x 200)	400mm (2 x 200)	options available in 190 or 200mm increments
Tread Surface (standard)	punched steel	punched steel	punched steel	option for PVC covered treads (or alloy chequer plate on HD)
Main Tubes	1" diam x 16g (1.5mm thick)	1" diam x 12g (2.5mm thick)	Rectangular Box 50 x 25 x 2mm	
Braking	to 6tr = 2 x spring loaded castors & 2 x 160mm wheels 7tr + = Ascent Safety Bar Narrow Aisle models = 4 x spring loaded castors	All sizes - Ascent Safety Bar	All sizes - Ascent Safety Bar	option for Side Lever instead of Ascent Safety Bar
Toeplates at Platform	up to 6tr = front toeplate only 7tr + = 3 sided toeplates	All sizes - 3 sided toeplates	All sizes - 3 sided toeplates	
Handrails	up to 6tr = no mid-height rail at platform 7tr + = mid-rail as standard	All sizes - Mid-height rail at platform as standard	All sizes - Mid-height rail at platform as standard	options available for gates, chains, bars etc at platform ; single-sided handrail or no handrail on stair
Finish	2tr - 12tr = epoxy powder coated (blue) 13tr + = wet paint finish unless supplied "knock-down"	epoxy powder coated (red)	epoxy powder coated (red)	colour options available (+ Hot-Dip Galvanised on HDuty & EasySlope)
Fabrication	Made in 1 piece & fully welded ("knock-down" option available)	3tr - 6tr = 1 piece welded as Medium Duty 7tr + = 3 pieces bolted together but supplied assembled for use	3tr - 6tr = 1 piece welded as Medium Duty 7tr + = 3 pieces bolted together but supplied assembled for use	
Safe Working Load	150kg	150kg	150kg	
"Knock-Down" models (Medium Duty)	normally supplied assembled for use ; if dismantle, needs spanners to bolt together in about 15 minutes ; NB this is NOT a 2 minute "fold-down" operation			
Availability	normally made to order in approx 2 weeks but often a few assorted models in stock			

fax : 0117 951 5682

tel : 0117 935 4664

www.ladders999.co.uk

sales@lansfordaccess.co.uk

