

# HiPod ALLOY PODIUM SAFETY STEPS



- ▶ Brilliant VALUE FOR MONEY!
- ▶ HiPOD Podium Steps are fabricated for safe site work where stepladders are no longer acceptable. The latest way to gain HSE approval for low-level work.
- ▶ Working heights from 2.00m up to 3.20m.
- ▶ HiPOD is a safe podium step for working at low levels, with 4 main platform heights of 460mm or 710mm or 960mm and at 1.21m all from the one unit.
- ▶ Ideal for one-man use - unfold the unit, fit the platform and start work!
- ▶ Fully manoeuvrable and easily rolled along either open or closed on four 360 degree swivel & locking castors.
- ▶ Easily portable and manoeuvrable, when open or closed, the unit passes easily through standard doorways and corridors.
- ▶ Lightweight at only 37kg yet robust for regular industrial use - max safe working load 175kg / 27.5st. Manufactured from same materials as in Industrial Alloy Towers under ISO9001.
- ▶ Access to platform via clip-on steps and hinged gate.
- ▶ Provides a working platform D<sub>x</sub>W 600mm x 500mm.

## " HiPod " ALLOY PODIUM SAFETY STEPS

code	Platform Heights	No. Platform Heights	Appx Working Heights	Max Dimension Open H x W x D	Platform Size	SWL max	Weight
HIPOD12	1.21m ; 0.96m 0.71m ; 0.46m	4	2.00m - 3.21m	2.22 x 0.68 x 1.20m	600 x 500mm	175kg / 27.5stones	37.5kg

Closed Size H x W x D : 1.97m x 0.40m x 1.20m

Taller models - "HIPOD EXTRA " see over

A current, detailed **price list**  
can be printed from our web site  
[www.ladders999.co.uk](http://www.ladders999.co.uk)



[www.ladders999.co.uk](http://www.ladders999.co.uk)

# HiPOD EXTRA ALLOY PODIUM SAFETY STEPS



- ▶ HiPOD EXTRA Podiums are a **TALLER** range fabricated for those who need **EXTRA HEIGHT** as well as safety.
- ▶ Working heights from 2.0m up to 4.0m. Stabilisers as shown are now supplied with **all** "EXTRA" models.
- ▶ HiPODs are safe podium steps with several platform heights in the one unit.
- ▶ Ideal for one-man use - unfold the unit, fit the platform, attach the stabilisers and start work!
- ▶ Fully manoeuvrable and easily rolled along either open or closed on four 360 degree swivel & locking castors.
- ▶ Max safe working load 175kg / 27.5st. Manufactured from same materials as in Industrial Alloy Towers.
- ▶ Access to platform via clip-on steps, horizontal rungs and hinged gate.
- ▶ Provides a working platform DxW 600mm x 500mm.

## " HiPOD EXTRA " ALLOY PODIUM SAFETY STEPS

code	Platform Heights	No. Platform Heights	Appx Working Heights	Max Dimension Open H x W x D	Platform Size	Stabilisers included?	Weight
HIPOD14	1.46m ; 1.21m ; 0.96m ; 0.71m ; 0.46m	5	2.00m - 3.46m	2.43 x 0.68 x 1.20m	600 x 500mm	Yes one pair	38kg
HIPOD17	1.71m ; 1.46m ; 1.21m ; 0.96m ; 0.71m ; 0.46m	6	2.00m - 3.71m	2.68 x 0.68 x 1.20m	600 x 500mm	Yes one pair	40kg
HIPOD20	1.96m ; 1.71m ; 1.46m ; 1.21m ; 0.96m ; 0.71m ; 0.46m	7	2.00m - 3.96m	2.93 x 0.68 x 1.20m	600 x 500mm	Yes one pair	42kg

SWL max 175kg / 27.5stones

See our excellent website at  
[www.ladders999.co.uk](http://www.ladders999.co.uk)

for prices of these and our huge range  
of ladders, steps, podium steps  
and scaffold towers



UNITS 2 & 10 CHANCEL CLOSE TRADING ESTATE  
EASTERN AVENUE **GLOUCESTER** GL4 3SN  
FAX : 01452 505580  
**TEL: 01452 520144**

[www.ladders999.co.uk](http://www.ladders999.co.uk) [sales@lansfordaccess.co.uk](mailto:sales@lansfordaccess.co.uk)

All prices, details and specifications are subject to change without notice and are those ruling at date of order. E&OE.