INDUSTRIAL DE-LUXE STAIRWAY LOFT LADDER




Highly suitable for many commercial applications.

Ideal for domestic use where a very safe and sturdy ladder is required.

Very popular with the elderly and others who need effortless operation, a rigid ladder and the safety of double handrails and extra wide treads.

Our best-selling & most popular alloy loft ladder!

- Very sturdy construction & full industrial duty.
- Kitemarked to BSEN14975 with a max safe load of 150kg (23.6 stones).
- Spring-counterbalanced action on nylon slides for smooth, silent, effortless operation. All of the weight is supported by the springs in the loft. Ladder raises and lowers with the trapdoor.
- Pivot arms and heavy duty springs attach to loft floor. Ladder also attaches to hatch edge and upper face of trap door.
- Two sections and fully interlocked.
- Extra-wide non-slip alloy treads are 3" (74mm) deep and heavily ribbed (83mm deep side stiles).
- Two large handrails fitted full length for maximum comfort and safety.
- Packed size -7'1" x 1'4" x 10".
- » Approx weight 19kg





INDUSTRIAL DE-LUXE STAIRWAY LOFT LADDER

INSTALLATION NOTES

EQUIPMENT SUPPLIED:

1 x YDLX loft Ladder c/w two springs mounted on timber board

- 2 x Handrails
- 1 x Operating Pole
- 1 x Trapdoor Catch
- 2 x Trapdoor Hinges

All necessary fixings & detailed Installation Guide

PREPARATION OF LOFT:

The De-Luxe Stairway must be well secured to the loft floor. Flooring grade chipboard is not adequate. It is recommended that a sheet of blockboard 1.0m x 0.5m x 25mm is used to reinforce the floor. It is also recommended that your trapdoor is at least 19mm / 3/4" thick plywood or blockboard. It must be hinged to swing vertically downwards.


FITTING PROCEDURE:


Although it is possible for experienced fitters to work alone, two people are recommended for parts of the installation. Always follow the detailed Installation Guide.

WILL IT FIT?

Note that the height measurements stated are the vertical heights between the loft floor and the floor in the room below. Please check your dimensions carefully before ordering to be certain this loft ladder is suitable for your premises. We are not able to accept the return of loft ladders which will not fit.







"INDUSTRIAL DE-LUXE STAIRWAY" ALLOY LOFT LADDER			
code	Min & Max FLOOR-TO-FLOOR Heights	Loft Clearance Arc (vertical x horizontal)	Minimum Trapdoor Size
YDLX	7'7" - 10'8"	40" x 63"	20" x 27"
	2.31m - 3.25m	1.03m x 1.60m	510mm x 690mm



See our excellent website at

www.ladders999.co.uk

for details of our huge range of ladders, steps, podium steps and scaffold towers



UNITS 2 & 10 CHANCEL CLOSE TRADING ESTATE

EASTERN AVENUE GLOUCESTER GL4 3SN FAX: 01452 505580

TEL: 01452 520144

www.ladders999.co.uk sales@lansfordaccess.co.uk

All prices, details and specifications are subject to change without notice and are those ruling at date of order, E&OE,