EASY-RISE Steel Mobile Safety Stairs

Shallow 48 degree slope for extra safety and comfort

Allows users to turn & descend facing forwards like a staircase

Much safer than standard models when carrying down heavy goods

BSI kitemarked BSEN131-7 max load 150kg

CAU ION! Tread Options Standard Punched Optional Anti-Slip Steel **PVC** Covered FAX: 01452 505580 TEL: 01452 520144 www.ladders999.co.uk sales@lansfordaccess.co.uk

National Sales Office - Units 2 & 10 Chancel Close, Eastern Avenue, GLOUCESTER GL4 3SN

EASY-RISE Steel Mobile Safety Stairs

۲

•





Large treads of robust Punched Steel are 760mm wide x 200mm deep for security and comfort (anti-slip PVC covered treads are available as an option at same price).

obiects.

Large platform 400mm deep is surrounded by a 950mm high handrail on three sides. Toeplates fitted around platform on all models.

High quality and very sturdy Safety Stairs manufactured in

Constructed from similar materials to our other models but

> an even shallower rake angle of just 48 degrees

These special features make ascent and descent even easier and safer - especially when carrying heavy

manoeuvring is plentiful (increased overall base length)

> a tread-to-tread height of just 230mm

Ideal where safety is paramount and space for

the UK from heavy grade tubular steel. Extremely safe, stable and robust in use.

with two important differences -

- Rubber tyred wheels 200mm diam fitted at the rear with 100mm swivelling castors at the front for easy manoeuvring. Roller bearings in all four.
- Braked by the side hand lever. When pushed back, the ۲ castors are automatically raised from the ground to stabilise the stair and rest on plastic floor pads. When pulled forwards the unit is fully mobile.
- Coated in a tough and attractive red epoxy-powder finish ▶ for long-lasting protection.
- Several optional extras are offered to enhance the standard ▶ range e.g. Anti-Slip PVC covered treads, Hinged Gates, Wire Baskets, etc.



Optional Hinged Gates can be fitted to end or either side & open inwards. Gates are spring loaded with plunger bolt closure. Side gates increase platform length and overall length by 360mm.

BSI kitemarked BSEN131-7 max load 150kg

EASY-RISE STEEL MOBILE SAFETY STAIRS						
CODE	No. Treads including platform	Platform Height	Tread Width mm / ft	Top Platform Size WxD	Overall Dimensions H x L x W (m)	Appx Weight
Top Platform Size WxD 760 x 400mm / 30" x 16"						
RHERS05	5	1.15m / 3' 9"	760 / 2' 6"	760 x 400mm	2.11 x 1.40 x 0.98	78kg
RHERS06	6	1.38m / 4' 6"	760 / 2' 6"	760 x 400mm	2.34 x 1.60 x 0.98	86kg
RHERS07	7	1.61m / 5' 3"	760 / 2' 6"	760 x 400mm	2.57 x 1.80 x 0.98	94kg
RHERS08	8	1.84m / 6' 0"	760 / 2' 6"	760 x 400mm	2.80 x 2.00 x 0.98	102kg
RHERS09	9	2.07m / 6' 10"	760 / 2' 6"	760 x 400mm	3.03 x 2.20 x 0.98	110kg
RHERS10	10	2.30m / 7' 7"	760 / 2' 6"	760 x 400mm	3.26 x 2.40 x 1.15	130kg
RHERS11	11	2.53m / 8' 4"	760 / 2' 6"	760 x 400mm	3.49 x 2.60 x 1.15	140kg
RHERS12	12	2.76m / 9' 1"	760 / 2' 6"	760 x 400mm	3.72 x 2.80 x 1.15	150kg
Optional Extras - please discuss with our helpful staff						
Treads are Punched Steel as standard — no cost option for Anti-Slip PVC Covered						

Freads are Punched Steel as standard — no cost option for Anti-Slip PVC Covered Optional Hinged Gates to Rear or LH or RH side ; NB. Side gates add extra 380/300mm to overall length Optional Hook-On Wire Basket LxWxD 600 x 220 x 220mm; max load 5kg Optional Hook-On Tool Tray LxWxD 600 x 250 x 220mm; max load 5kg

> Full details and prices are on our website www.ladders999.co.uk

FAX: 01452 505580 TEL: 01452 520144

www.ladders999.co.uk





National Sales Office - Units 2 & 10 Chancel Close, Eastern Avenue, GLOUCESTER GL4 3SN