

Fort® Tilt & Pull Steps

- » Available as a standard version or as a model which is Certified to BS EN 14183
- » Tread size: 400 x 150mm
- » Top tread size: 400 x 200mm
- » Wheels fitted at front enabling the steps to be tilted forwards
- » Fitted with rubber feet & 2 x 75mm grey rubber tyred wheels
- » Standard version fitted with resilient anti-slip treads with tread clamps. Available in blue only.
- » BS EN 14183 version is fitted with phenolic non-slip treads. Frame available in red, blue, yellow or green - please specify when ordering

FROM ONLY

£165.60



Safety, Strength & Durability



BS EN 14183 COLOUR OPTIONS

- Red
- Blue
- Yellow
- Green

specify when ordering



BS EN 14183 Model GS2003R



BS EN 14183 Model GS2004R



WS2002, WS2003 & WS2004

Resilient anti-slip treads with tread clamps

Resilient anti-slip treads which are clamped to the steel tread by a high visibility yellow strip to prevent the edges peeling



No. of Treads	Platform Height mm	Overall Size H x W x D mm	Weight kg	Model	Price
Standard Version - Anti-slip treads with Tread Clamps					
2	500	1050 x 470 x 630	10	WS2002	£165.60
3	750	1300 x 490 x 800	12	WS2003	£212.80
4	1000	1700 x 565 x 1005	16	WS2004	£284.50
BS EN 14183 Version - Phenolic Non-slip Treads					
2	470	1070 x 490 x 580	10	GS2002R	£251.00
3	705	1410 x 520 x 745	12	GS2003R	£334.45
4	940	1650 x 540 x 910	16	GS2004R	£443.40

Standard Model WS2003 - Tilted