

" SINGLE SECTION " Industrial Alloy Ladders



SINGLE SECTION Alloy Ladders - round rungs
Made to BS2037 Class1 Industrial Duty - not kitemarked

Code	Closed Height	Rung Type	No Rungs	Weight
CLS1010	1.00m / 3' 3"	Round	4	1.5
CLS1012	1.25m / 4' 1"	Round	5	1.9
CLS1015	1.50m / 4' 11"	Round	6	2.3
CLS1017	1.75m / 5' 9"	Round	7	2.7
CLS1020	2.00m / 6' 6"	Round	8	3.1
CLS1022	2.25m / 7' 4"	Round	9	3.4
CLS1025	2.50m / 8' 2"	Round	10	3.8
CLS1027	2.75m / 9' 0"	Round	11	4.2
CLS1030	3.00m / 9' 10"	Round	12	4.6
CLS1032	3.25m / 10' 8"	Round	13	5.0
CLS1035	3.50m / 11' 6"	Round	14	5.4
CLS1037	3.75m / 12' 4"	Round	15	6.7
CLS1040	4.0m / 13' 1"	Round	16	8.1

SINGLE SECTION Alloy Ladders - round rungs
Made to BS2037 Class1 Industrial Duty - not kitemarked

Code	Closed Height	Rung Type	No Rungs	Weight
RGS115	1.55m / 5' 1"	Round	6	3.0
RGS120	2.05m / 6' 9"	Round	8	4.0
RGS125	2.55m / 8' 4"	Round	10	5.0
RGS130	3.05m / 10' 0"	Round	12	6.0
RGS135	3.55m / 11' 8"	Round	14	7.0
RGS140	4.05m / 13' 4"	Round	16	8.0
RGS145	4.55m / 14' 11"	Round	18	9.0
RGS150	5.05m / 16' 7"	Round	20	12.0
RGS155	5.55m / 18' 3"	Round	22	16.0
RGS160	6.05m / 19' 10"	Round	24	18.0
RGS170	7.05m / 23' 2"	Round	28	20.0

- ▶ SINGLE Section Alloy Ladders to BS Class 1 for a variety of specialist applications around the workplace.
- ▶ These Heavy Duty "Class 1 Industrial" ladders are designed for years of rigorous service.
- ▶ All are made to the strongest Industrial Duty BS2307 Class 1 with a Maximum Safe Load 175kg (27.5stones). Duty rating 130kg (20.5stones). BS2037 is now withdrawn so none are kitemarked but all are still made to that same strength & durability standard.
- ▶ Side stiles are of box-section alloy which is graded in size according to the ladder length. Solid moulded rubber bungs fitted at top and bottom.
- ▶ Our **CLS range has 25mm diameter alloy Round Rungs** which are heavily ribbed for non-slip safety.
- ▶ These ladders are industrial duty and represent an economical solution to many access problems. These are suitable for all uses whether used vertically or at any other angle because footing angles remain the same in all cases. Overall width 330mm. Rung Spacing 250mm.
- ▶ Our **RGS range has 25mm diameter alloy Round Rungs** which are heavily ribbed for non-slip safety. These are suitable for all uses whether used vertically or at any other angle because footing angles remain the same in all cases. Overall width 325mm. Rung Spacing 250mm.
- ▶ Specials with bespoke modifications are optional for all ranges.

See our excellent website at
www.ladders999.co.uk

for prices of these and our huge range
of ladders, steps, podium steps
and scaffold towers



UNITS 2 & 10 CHANCEL CLOSE TRADING ESTATE
EASTERN AVENUE **GLOUCESTER** GL4 3SN
FAX : 01452 505580
TEL: 01452 520144

www.ladders999.co.uk sales@lansfordaccess.co.uk

All prices, details and specifications are subject to change without notice and are those ruling at date of order. E&OE.

“ SINGLE SECTION “ Industrial Alloy Ladders



GS RANGE WITH “ ANGLED FLAT-TOP D RUNGS “

SINGLE SECTION Alloy Ladders - D Type rungs
Made to BS2037 Class1 Industrial Duty - not kitemarked

Code	Closed Height	Rung Type	No Rungs	Weight
GS120	1.93m / 6' 4"	“D” type	7	4.0
GS125	2.43m / 8' 0"	“D” type	9	5.0
GS130	2.93m / 9' 8"	“D” type	11	6.0
GS135	3.43m / 11' 3"	“D” type	13	8.0
GS140	3.93m / 12' 11"	“D” type	15	9.0
GS145	4.43m / 14' 7"	“D” type	17	10.0
GS150	4.93m / 16' 2"	“D” type	19	11.0
GS155	5.43m / 17' 10"	“D” type	21	12.0
GS160	5.93m / 19' 6"	“D” type	23	13.0

- ▶ SINGLE Section Alloy Ladders to BS Class 1 for a variety of specialist applications around the workplace.
- ▶ These Heavy Duty "Class 1 Industrial" ladders are designed for years of rigorous service.
- ▶ All are made to the strongest Industrial Duty BS2307 Class 1 with a Maximum Safe Load 175kg (27.5stones). Duty rating 130kg (20.5stones). BS2037 is now withdrawn but these ladders are still made to that same strength & durability standard.
- ▶ Two of our ranges - **GS** range and **RGS** range are fully tested and BSI kitemarked whereas our **CLS** range is "made to" Class 1 but is not kitemarked.
- ▶ Side stiles are of box-section alloy which is graded in size according to the ladder length.
- ▶ Solid moulded rubber bungs fitted at top and bottom.
- ▶ Our **GS range has angled Flat-Top D-shaped alloy rungs** which are heavily ribbed for non-slip safety and are angled so that feet rest on wide surface during ascent & descent.
- ▶ These are most suitable for general use where used leaning at an angle.
- ▶ They are NOT very suitable for vertical or shallow angle applications which might result in unsafe footing angles. Overall width 375mm. Rung Spacing 250mm.
- ▶ Specials with bespoke modifications are optional for all ranges - please call to discuss.
- ▶ Normally made-to-order and delivered in 7 - 14 days. A few selected sizes in stock.

See our excellent website at
www.ladders999.co.uk

for prices of these and our huge range
of ladders, steps, podium steps
and scaffold towers



UNITS 2 & 10 CHANCEL CLOSE TRADING ESTATE
EASTERN AVENUE **GLOUCESTER** GL4 3SN
FAX : 01452 505580
TEL: 01452 520144

www.ladders999.co.uk sales@lansfordaccess.co.uk